


A SERIES LED PANEL LIGHT 40W

Mode: LG-PL-30120-40W-ModeA

LED LIGHT SOURCE



STANDARD



on request



DESCRIPTION

MOUNTING

Suspended / Surface / Recessed

LIGHT SOURCE

LED

OPTICAL SYSTEM

Diffuser

MATERIALS

Housing - aluminium

Diffuser - Light Guide

WIRING

Electronic control gear TRIDONIC

On request: dimmable electronic control gear (DALI)

LIGHT DISTRIBUTION

Direct

SURFACE FINISH

Housing - White mat color or Silvery

other colors on request

Advantages

- Color rendering index >80 Ra
- Color temperature 2700-7000K
- Durable and Long service life
- No Infrared radiation
- No UV rays
- Can be easily controlled and programmed
- IP40 Ingress protection
- 50,000 hrs lifetime

Driver:

Driver with metal box driver is provided, with ground-line.



Emergency Mode

On request, 30% brightness, 3 hours back-up



energy saving



eco friendly



maintenance free



no UV/IR rays


A SERIES LED PANEL LIGHT 40W

Mode: LG-PL-30120-40W-ModeA

LED LIGHT SOURCE



SIZE



COLOR TEMPERATURE

Warm White : 2800-3500K

Neutral White:4000-4500K

Daylight White:5000-5500K



Pure White: 6000-6500K

SPECIFICATION

Beam Angle:120degree

NO.	Model	LED	Watt	Voltage(V)	Lumen(lm)	CRI	PF	Out-dia
1	LG-PL-30120-40W-ModeA	SMD	40W	100~240	4200	≥ 80	≥ 0.95	295*1195*10mm

Photometric Data



REMARK

Mareli Ltd. reserves the right to introduce structural changes and modify the luminaires

Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of color temperature: +/-150 K.

Unless stated otherwise, the values apply to an ambient temperature of 25° C

A SERIES LED PANEL LIGHT 40W

Mode: LG-PL-30120-40W-ModeA



LED LIGHT SOURCE



Products advantages

- With the pure aluminum alloy ,excellent eletionational dissipation
- Thin design which no room,beautiful clothing
- SPECIAL electional design ,ensure every LED work separate,no effection for each other
- Adopt the eletional panel ,ensure light uniform easily,improve the light effectiom
- No dissipation, anti-lightspot which ensure reasonable light effection
- Fix easily which can used for wall and instead of ceil
- Mainly used for hotel, business place, iving room, articture

INSTALLATION DRAWING



Install The Matters Needing Attention

- 1.Only professional electrician can install the lamp.
- 2.Check the lamp very carefully before installation.
- 3.Install the lamp follow up the installation procedure, make sure all parts safe.
- 4.Please request after service if trouble or doubt.

Areas of application

